What is claimed is:

1. A multilayer structure on a bottom of a contact hole, said multilayer structure comprising a titanium film on a silicon region and a titanium nitride film on said titanium film.

wherein said titanium nitride film has a compressive stress of not higher than $5{\times}10^9$ dyne/cm² so that said titanium film has such a high stability as preventing any crack upon changing said compressive stress to a tensile stress by a heat treatment.

- 2. The multilayer structure as claimed in claim 1, wherein said compressive stress of said titanium nitride film is not higher than 3×109 dyne/cm².
- 3. The multilayer structure as claimed in claim 1, wherein said titanium nitride film is mainly oriented in a (200)-face.
- 4. The multilayer structure as claimed in claim 1, wherein said contact hole has an aspect ratio of not less than 4.
- 5. The multilayer structure as claimed in claim 4, wherein said contact hole has an aspect ratio of not less than 5.
- A contact plug structure in a contact hole in an inter-layer insulator on a silicon substrate, said contact plug structure comprising:
 - a titanium film on a bottom and a side wall of said contact hole;
 - a titanium nitride film on said titanium film;
- a metal plug on said titanium nitride film so that said metal plug buries said contact hole ; and $\,$
- a titanium silicide layer in a surface region of said silicon substrate and in contact with a bottom of said contact hole,
- wherein said titanium nitride film free of any crack and has a tensile stress of not higher than $3\!\times\!10^9$ dyne/cm².
- 7. The contact plug structure as claimed in claim 6, wherein said tensile stress of said titanium nitride film is not higher than 2×10^9

dyne/cm2.

- 8. The contact plug structure as claimed in claim 6, wherein said titanium nitride film is mainly oriented in a (200)-face.
- 9. The contact plug structure as claimed in claim 6, wherein said contact hole has an aspect ratio of not less than 4.
- 10. The contact plug structure as claimed in claim 9, wherein said contact hole has an aspect ratio of not less than 5.